



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
-----------------	-------------	----------------------	---------------------	------------------

10/764,693

01/26/2004

Roberto Puon

710101.1260

9183

21491 7590 06/22/2009  
LANIER FORD SHAVER & PAYNE P.C.  
P O BOX 2087  
HUNTSVILLE, AL 35804-2087

EXAMINER

TODD, GREGORY G

ART UNIT

PAPER NUMBER

2457

MAIL DATE

DELIVERY MODE

06/22/2009

PAPER

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

<b>Office Action Summary</b>	<b>Application No.</b> 10/764,693	<b>Applicant(s)</b> PUON ET AL.	
	<b>Examiner</b> GREGORY G. TODD	<b>Art Unit</b> 2457	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

### Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

### Status

- 1) ☒ Responsive to communication(s) filed on 04 June 2009.
- 2a) ☐ This action is **FINAL**.                      2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

### Disposition of Claims

- 4) ☒ Claim(s) 1-8 and 10-19 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1-8 and 10-19 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

### Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on \_\_\_\_\_ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

### Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All    b) ☐ Some \*    c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
  2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

### Attachment(s)

- |  |   |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892)                                | 4) <input type="checkbox"/> Interview Summary (PTO-413)<br>Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948)                       | 5) <input type="checkbox"/> Notice of Informal Patent Application                       |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)<br>Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____  |

## **DETAILED ACTION**

### ***Response to Amendment***

1. This office action is in response to applicant's amendment and request for continued examination filed, 04 June 2009, of application filed, with the above serial number, on 26 January 2004 in which claims 1, 6, 11-12, 16, and 19 have been amended. Claims 1-8 and 10-19 are pending in the application.

### ***Claim Rejections - 35 USC § 103***

2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

3. Claims 1-2, 4-8, 10-12, and 14-19 are rejected under 35 U.S.C. 103(a) as being unpatentable over Gale et al (hereinafter "Gale", 6,868,509) in view of Heeren et al (hereinafter "Heeren", 6,311,288) and Dantu et al (hereinafter "Dantu", 7,167,443).

As per Claim 1, Gale teaches a network router, comprising:

memory (at least col. 6:4-29);

a layer 1 portion having a first communication interface and a second communication interface (at least col. 5:46-54; col. 7:36-63; col. 6:15-29; Fig. 3; router w/ 2 comm. ports connected to network connections);

a layer 2 portion (at least col. 6:15-64; communication stacks);

a layer 3 portion having a layer 3 protocol stack (at least col. 6:15-29), said layer 3 protocol stack having a routing table stored in said memory and specifying, for a particular destination, a data path from said layer 3 portion to said layer 2 portion, said layer 3 protocol stack configured to provide a plurality of data packets destined for the particular destination and to route through said data path each of said data packets based on said routing table (at least col. 6:15-64; routing table); and

switching logic configured to automatically initiate a layer 2 switch such that said layer 2 portion interfaces a plurality of said data packets with said second communication interface in lieu of said first communication interface, wherein said layer 2 portion is configured to interface at least one of said data packets with said first communication interface prior to said layer 2 switch (at least col. 5:30-35; col. 6:15-64; fault router using networking/switch logic to route communications to non-faulted network from faulted/primary network), wherein said first communication interface is configured to transmit said at least one data packet to a second router over a first data path through a first network, and wherein said second communication interface is configured to transmit said plurality of said data packets to said second router over a second data path through a second network (at least col. 5:30-35; col. 6:15-64; non-faulted network from faulted/primary network).

Gale fails explicitly teaching wherein said layer 2 switch is transparent to said layer 3 portion and the communication interfaces are configured to transmit via a first and second protocol. However, the use and advantages for using such a system is well known to one skilled in the art at the time the invention was made as evidenced by the

teachings of Heeren. Heeren teaches a communications device (FRAU 12) detecting a link failure and providing access to a parallel backup path on another network using another protocol and being transparent to routers and other communications devices, thereby quickly establishing a backup link to continue transport of the information (at least col. 4:25-37; Fig. 1, 2; col. 6:49-57; 9:45-54). Therefore, it would have been obvious to one of ordinary skill in the art, at the time the invention was made, to incorporate Heeren's transparent backup network with Gale's system as Heeren teaches it is advantageous to quickly establish a backup link to continue the transport of information without rerouting all the information to be transmitted and the backup networks such as ISDN and PSTN as simply being alternate, thereby complementing Gale's redundant network protocols (col. 5:46-54) as the substitution of one known protocol or network for another would have yielded predictable results to one of ordinary skill in the art at the time of the invention.

Gale and Hereen fail to explicitly teach said layer 3 protocol stack further configured to detect an error condition and the respective layer 2 switch for said layer 2 portion of said network router in response to such error condition. However, the use and advantages for using such a system is well known to one skilled in the art at the time the invention was made as evidenced by the teachings of Dantu. Dantu teaches communication link failure at layer 1, 2, or 3 being detected at the layer 3 and signaled to other routers, and associated switching of layer 1 and 2 in response from the working path to the protection path from the central IP router or router 204 (at least col. 7:48-8:33; col. 18:11-25). Therefore, it would have been obvious to one of ordinary skill in the

art, at the time the invention was made, to incorporate the use of Dantu's signaling with Gale and Heeren as Dantu teaches it enables a communication link failure to be detected and responded to faster (col. 8:27-33) than conventional layer 3 error conditions are found.

As per Claim 2. Gale fails to explicitly teach wherein said switching logic is further configured to automatically initiate another layer 2 switch, in response to a detection that said error condition is resolved, such that said layer 2 portion interfaces a second plurality of said data packets with said first communication interface in lieu of said second communication interface. However, the use and advantages for using such a system is well known to one skilled in the art at the time the invention was made as evidenced by the teachings of Heeren. Heeren teaches rerouting along the backup network until the primary network is again fully available (at least col. 9:47-54).

Therefore, it would have been obvious to one of ordinary skill in the art, at the time the invention was made, as all the claimed elements were known in the prior art and one skilled in the art could have combined the elements as claimed by known methods with no change in their respective functions, and the combination would have yielded predictable results to one of ordinary skill at the time of the invention.

As per Claim 4. The router of claim 1, wherein said first data path comprises a T1 link (at least col. 5:46-54).

As per Claim 5. Gale fails to teach wherein said second communication interface comprises a modem. However, the use and advantages for using such a system is well

known to one skilled in the art at the time the invention was made as evidenced by the teachings of Heeren. Heeren teaches using a modem for the backup path (at least col. 6:49-60). Therefore, it would have been obvious to one of ordinary skill in the art, at the time the invention was made, to substitute the use of Heeren's modem with Gale's second communication port as seen above, Heeren's backup network paths could be used with a modem based on design choice to provide access with that network protocol.

As per Claim 6, Gale teaches a network router, comprising:

memory (at least col. 6:4-29);

a layer 3 protocol stack configured to provide a plurality of data packets to be transmitted by said network router to a second router, the layer 3 protocol stack having a routing table stored in said memory and specifying a data path for routing said plurality of data packets to said second router, the layer 3 protocol stack configured to insert, into each of said plurality of data packets, route information indicative of said data path based on said routing table (at least col. 6:15-64; Fig. 3; router and communication stacks with routing table);

a first layer 2 protocol stack; a second layer 2 protocol stack (at least col. 6:15-64; communication stacks);

a plurality of layer 3 network interfaces configured to receive data packets from said layer 3 protocol stack, wherein said layer 3 protocol stack is configured to provide each of said plurality of data packets to one of said layer 3 network interfaces (at least col.

5:46-54; col. 7:36-63; col. 6:15-29; Fig. 3; fault router w/ 2 comm. ports connected to network connections); and

layer 2 switching logic configured to receive each of said plurality of data packets from said one layer 3 network interface, said layer 2 switching logic configured to provide at least one of said plurality of data packets to said first layer 2 protocol stack such that said at least one of said plurality of data packets is transmitted via a primary network, said layer 2 switching logic configured to perform a layer 2 switch in response to a detection of an error condition such that said layer 2 switching logic provides, in response to said detection, at least one other of said plurality of data packets to said second layer 2 protocol stack such that said at least one other of said plurality of data packets is transmitted via a secondary network (at least col. 5:30-35; col. 6:15-64; fault router using networking/switch logic to route communications to non-faulted network from faulted network).

Gale fails explicitly teaching wherein said layer 2 switch is transparent to said layer 3 portion and the communication interfaces are configured to transmit via a first and second protocol. However, the use and advantages for using such a system is well known to one skilled in the art at the time the invention was made as evidenced by the teachings of Heeren. Heeren teaches a communications device (FRAU 12) detecting a link failure and providing access to a parallel backup path on another network using another protocol and being transparent to routers and other communications devices, thereby quickly establishing a backup link to continue transport of the information (at least col. 4:25-37; Fig. 1, 2; col. 6:49-57; 9:45-54). Therefore, it would have been

obvious to one of ordinary skill in the art, at the time the invention was made, to incorporate Heeren's transparent backup network with Gale's system as Heeren teaches it is advantageous to quickly establish a backup link to continue the transport of information without rerouting all the information to be transmitted and the backup networks such as ISDN and PSTN as simply being alternate, thereby complementing Gale's redundant network protocols (col. 5:46-54) as the substitution of one known protocol or network for another would have yielded predictable results to one of ordinary skill in the art at the time of the invention.

Gale and Hereen fail to explicitly teach the layer 3 protocol stack further configured to detect an error condition and the respective layer 2 switch in said network router in response to such error condition. However, the use and advantages for using such a system is well known to one skilled in the art at the time the invention was made as evidenced by the teachings of Dantu. Dantu teaches communication link failure at layer 1, 2, or 3 being detected at the layer 3 and signaled to other routers, and associated switching of layer 1 and 2 in response from the working path to the protection path from the central IP router or router 204 (at least col. 7:48-8:33; col. 18:11-25). Therefore, it would have been obvious to one of ordinary skill in the art, at the time the invention was made, to incorporate the use of Dantu's signaling with Gale and Hereen as Dantu teaches it enables a communication link failure to be detected and responded to faster (col. 8:27-33) than conventional layer 3 error conditions are found.

As per Claim 7. The system of claim 6, further comprising: a first communication interface configured to transmit, over said primary network to said second router, each of said plurality of data packets provided to said first layer 2 protocol stack; and a second communication interface configured to transmit, over said secondary network to said second router, each of said plurality of data packets provided to said second layer 2 protocol stack (at least col. 6:15-64; routing table for routing to respective network).

As per Claim 8. The system of claim 7, wherein said protocol stacks, said network interfaces, said switching logic, and said communication interfaces are each integrated within a housing unit (at least Fig. 3:313; col. 6:15-29; fault router).

As per Claim 17. The router of claim 1, wherein said layer 3 portion is configured to insert, into each of said data packets, the same route information based on said routing table (at least col. 6:15-64; routing table for routing to respective network).

As per Claim 18. The router of claim 1, wherein said second data path is a dedicated path from said network router to said second router (at least Heeren Fig. 1).

Claims 10-12, 14-16, and 19 do not add or define, in substance, any additional limitations over claims 1-2, 4-8, and 17-18 and therefore are rejected for similar reasons.

4. Claims 3 and 13 are rejected under 35 U.S.C. 103(a) as being unpatentable over Gale in view of Heeren and Dantu, further in view of Singh et al (hereinafter "Singh", 2003/0088698).

Gale Heeren, and Dantu fail to teach wherein said second communication interface is configured to communicate using point-to-point protocol (PPP). However, the use and advantages for using such a system is well known to one skilled in the art at the time the invention was made as evidenced by the teachings of Singh. Singh teaches using PPP communication (at least paragraph 16). Therefore, it would have been obvious to one of ordinary skill in the art, at the time the invention was made, to substitute the use of one known element, PPP of Singh, for another, with the network types of Gale (at least col. 5:45-54).

### ***Response to Arguments***

5. Applicant's arguments filed 04 June 2009 have been fully considered but they are not persuasive.

Applicant argues Dantu does not teach performing a "layer 2 switch" in response to a detection of a "layer 3 condition". In response to applicant's argument that the references fail to show certain features of applicant's invention, it is noted that the features upon which applicant relies (i.e., layer 3 condition) are not recited in the rejected claim(s). Although the claims are interpreted in light of the specification, limitations from the specification are not read into the claims. See *In re Van Geuns*, 988 F.2d 1181, 26 USPQ2d 1057 (Fed. Cir. 1993). While this may be the intent of the Applicant, this is not what is being claimed. The claims merely teach the layer 3 portion detecting an error condition (supposedly at any layer), and initiating a layer 2 switch upon any layer error condition. Dantu clearly teaches that the *layer 3 portion detects*

error conditions at any layers and transparent protection switching at layer 1 *and layer 2* from a working path (first interface) to a protection path (second interface) in response (col. 7:48-8:33).

Applicant further argues Dantu does not teach such switching occurring on the same router. However, such transparent switching clearly occurs on the same central IP router and/or router 204, and when router 208, or the path 208 is on, has an error condition, switching to the protection path with router 216, for example (see Fig. 2; col. 7:48-8:33).

### ***Conclusion***

6. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure. Newly cited Nguyen and Puon et al, in addition to previously cited Ueno et al, Li, Riggan et al, Farris, Jones, Joseph et al and Shew et al, are cited for disclosing pertinent information related to the claimed invention. Applicants are requested to consider the prior art references for relevant teachings when responding to this office action.

7. Any inquiry concerning this communication or earlier communications from the examiner should be directed to GREGORY G. TODD whose telephone number is (571)272-4011. The examiner can normally be reached on Monday - Friday 9:00am-5:30pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Ario Etienne can be reached on (571)272-4001. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/G. G. T./  
Examiner, Art Unit 2457  
/Salad Abdullahi/  
Primary Examiner, Art Unit 2457